



MIOTTI



KTY 84-130



SERIES : KTY 84-130	SENSOR: NXP KTY 84-130 (or substitute)
INSULATING CAP : Double cap of heat-shrinkable PTFE (length 20mm) Dielectric Strength 2 KV AC	CABLE : Copper braid, MFA insulation, AWG 24, external diameter 1.05 mm \pm 0.10 mm Dielectric Strength 2 KV AC
CABLE COLOR : Black – Red	TERMINAL CONNECTORS : On request
CONNECTION CABLE/CAPSULE: Vulcanized Thermoplastic Rubber	NOTES : Avoid applying pressure to the sensor. Use special care when inserted in motor windings. Use only appropriate digital readers (maximum current 2mA)
CAUTION: This device is sensitive to ElectroStatic Discharge (ESD). Therefore care should be taken during transport and handling	
TEMPERATURE RANGE : 0 ° C a 250 ° C for standard application Impregnation will result in a better stability at lower temperatures	IP : IP 55



MIOTTI

Miotti Rappresentanze srl

Viale del Lavoro, 22 · 36100 Vicenza · Tel. +39 0444 563611 · Fax. +39 0444 961545 · info@miottisrl.com · www.miottisrl.com

ST/18 R01 – 07/10/2015